



DLR-970-2000

High Brightness Diode Laser

NEW PRODUCT





Applications

- Optical Pumping
- ▶ Plastics Welding
- ▶ Metal Hardening
- ▶ Soft Soldering
- ▶ Brazing
- ▶ FPD Bonding
- ▶ Silicon Surface Modification



Features

- ▶ Output Power up to 2.0 kW
- ▶ High Brightness
- ▶ Modulated up to 50 kHz
- ➤ Stabilized Central Wavelength
- ▶ Narrow Emission Linewidth
- ► Compact and Low Cost
- ► High Wall-plug Efficiency
- ► Industrial Performance

IPG Photonics' DLR 970 Series industrial grade high power diode laser system provides 970 +/-10 nm emission combined in various power levels up to 2 kW. IPG's advanced technology is based on highly reliable entirely sealed high efficiency single-emitter diodes. The wall-plug efficiency of the DLR-970 system approaches 35%. IPG's DLR 970 diode laser is brighter, higher quality and more reliable than any other diode laser on the market. Air or water-cooled, this compact platform is cost-effective and virtually maintenance-free. DLR-970 lasers are used in soft soldering, metal hardening, plastics welding, silicon surface modification and FPD bonding, and are also an ideal source for optical laser pumping.



DLR-970-2000

High Brightness Diode Laser

| Optical Characteristics | DLR-100 | DLR-300 | DLR-500 | DLR-1000 | DLR-1500 | DLR-2000 | | |
|--------------------------------|--------------|---------|---------|----------|----------|----------|--|--|
| Wavelength, nm | 970 ±10 | | | | | | | |
| Linewidth FWHM, nm | 5 | | | | | | | |
| Mode of Operation | CW/Modulated | | | | | | | |
| Modulation Frequency, kHz | 0-50 | | | | | | | |
| Average Power, W | 100 | 300 | 600 | 1000 | 1500 | 2000 | | |
| Power Tunability, % | 10-100 | | | | | | | |
| Power Stability*, % | ±1 | | | | | | | |
| Optical Noise**, % RMS | 1 | | | | | | | |
| Output Fiber Core Diameter, μm | 200 | | 300 | | 400 | | | |
| Output Fiber NA | <0.22 | | | | | | | |

^{*}Over 4 hours, T= ±1°C

^{**10} kHz - 20 MHz

| General Characteristics | | | | | | | | | | | |
|--|-------------------|------|-------------------|-------|-----------------|-------|--|--|--|--|--|
| Cabinet Dimensions (W \times D \times H), mm | 448 × 403 × 132 | | 448 × 580 × 132 | | 448 × 677 × 177 | | | | | | |
| Cooling | Air-cooled | | Water-cooled | | | | | | | | |
| Supply Voltage, VAC | 100-240, 50-60 Hz | | 200-240, 50-60 Hz | | | | | | | | |
| Power Consumption, W | <300 | <900 | <1800 | <3000 | <4500 | <6000 | | | | | |

+1 (508) 373-1100; sales.us@ipgphotonics.com

+49 2736 44200; sales.europe@ipgphotonics.com (European Inquiries)

www.ipgphotonics.com

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2013-19 IPG Photonics Corporation. All rights reserved.



DANGER - INVISIBLE LASER
RADIATION AVOID EYE OR SKIN
EXPOSURE TO DIRECT OR
SCATTERED RADIATION
CLASS 4 LASER PRODUCT
IEC 60825-1:2014