




YLM-600/6000-QCW-MM

Multi-mode Quasi-CW Fiber Laser

NEW PRODUCT

6 kW Peak Power Module



Applications

- ▶ Replacement for Lamp-pumped Lasers
- ▶ Spot Welding
- ▶ Seam Welding
- ▶ Microwelding
- ▶ Drilling
- ▶ Cutting
- ▶ Batteries
- ▶ Medical Devices
- ▶ Computer Components



Features

- ▶ Outstanding Pulse Power/ Energy Stability
- ▶ >30% Wall-plug Efficiency
- ▶ CW and Pulsed Modes
- ▶ Beam Quality Optimized for Applications
- ▶ Internal Pulse Generator and Pulse Shaping
- ▶ Low Cost High Peak Power

IPG has expanded its quasi continuous wave (QCW) fiber laser series to higher power models including the NEW **YLM-600/6000-QCW-MM** laser. The new modules are more powerful and feature compact size and lower price per Watt. Short modulation time and temporal pulse shaping enable improved control and quality in micromachining applications. The QCW fiber lasers are ideal for spot welding, drilling and cutting in the long pulse operation mode. These compact units are substantially more cost-effective than conventional YAG lasers due to >30% wall-plug efficiency and maintenance-free operation. The QCW fiber lasers are available for requalifying existing lamp-pumped processes. Retrofit services, including engineers familiar with system integration, are available to help customers replace older production lasers with energy-efficient fiber lasers from IPG.

YLM-600/6000-QCW-MM

Multi-mode Quasi-CW Fiber Laser

Optical Characteristics

Wavelength, nm	1070 ±5
Mode of Operation	Pulsed/CW
Modulation Frequency, kHz	0-50
Max. Average Power, W	600
Max. Peak Power, W	6000
Max. Pulse Energy, J	60
Pulse Duration*, ms	0.05-50
Power Tunability, %	10-100
Power Stability**, %	±0.5
Output Fiber Core Diameter, μm	50, 100, 200
Beam Parameter Product, mm × mrad	2.5, 5, 10

* The minimum pulse duration is 10 microseconds upon request

** Over 4 hours, T=const



General Characteristics

	YLM-600/6000-QCW-MM-AC	YLM-600/6000-QCW-MM-WC
Dimensions (W × D × H), mm	416 × 566 × 148	411 × 509 × 85
Weight, kg	<35	
Cooling	Air-cooled	Water-cooled
Supply Voltage, VDC	48	
Power Consumption, W	<2100	

+1 (508) 373-1100; sales.us@ipgphotonics.com
 +49 2736 44200; sales.europe@ipgphotonics.com (European Inquiries)

www.ipgphotonics.com

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2011-19 IPG Photonics Corporation. All rights reserved. US Patent 7,873,085



The Power to Transform®